



HEXOL SYNLINER SUPERDIESEL 5W30

MOTOR OIL

PRODUCT DESCRIPTION

Hexol Synliner Superdiesel 5w30 is an extra high performance, low SAPS, fuel saving, synthetic engine oil assuring long drain intervals. Produced from synthetic base oils and a complex additive system, it ensures excellent flow characteristics. Recommended to be used in the most advanced diesel or gasoline, naturally aspirated or turbocharged engines, including "Pumpe-Düse" (PD), fitted with or without diesel particulate filters (DPF) or three-way catalysts. This oil exceeds requirements of the most important European and US automobile associations and engine manufacturers such as: Renault, Mercedes, Peugeot, Porsche, Volkswagen, Fiat, Opel, Citroen, BMW, Ford, Toyota, Hyundai and others.

PERFORMANCE FEATURES

- Exceeds ACEA C3-12, ACEA A3/B4, API Service CF/SN and CF/SM requirements,
- Meets standard requirements imposed by renowned automakers such as BMW Longlife-04, VW 502.00/505.00/505 01, Porsche C30, Fiat 9.55535-S2, MB 229.51 and many others,
- Extra long oil drain interval,
- Extra high performance oil providing long engine life,
- Provides reliable start-up and operation even at extremely low temperatures,
- Low SAPS lubricant, guarantees a long lifetime of exhaust gas treatment devices,
- This oil maintains its properties for up to 5 years when in its original container, sealed, and stored away from any heat source and direct sunlight (storage temperature max. 40°C).

APPLICATION

- Suitable for personal cars, vans and light commercial vehicles equipped with naturally aspirated or turbocharged, including "Pumpe-Düse" (PD), diesel or gasoline engines, fitted with or without Diesel Particulate Filters (DPF) or three-way catalysts, where the manufacturer recommends oil with the above listed properties,
- It has a long drain interval, depending on the engine manufacturer's recommendation.

PROPERTIES

Viscosity Grade SAE	5W30
Density at 15°C [kg/m ³]	850
Kinematic Viscosity at 100°C [mm ² /s]	9.3-12.5
Viscosity Index, min	150
Flash Point [°C] min	220
Pour Point [°C] max	-33

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input checked="" type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input checked="" type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L

HEXOL INTERNATIONAL LTD

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.
2019