



HEXOL SYNLINE ATF TORSION

AUTOMATIC TRANSMISSION OIL

PRODUCT DESCRIPTION

HEXOL Synline ATF Torsion is a high-quality synthetic automatic transmission oil, recommended for cars, vans or any other industrial equipment. It has pronounced anti-wear properties and excellent fluidity at low temperatures. It can also be used in hydraulic systems.

PERFORMANCE FEATURES

- can be used for specifications GM DEXRON® III-H, III-G, III-F, III-E, III-D, Ford MERCON®, Ford M2C138-CJ, M2C 166-H Fluids, Allison C-4 Fluids, Allison TES 389, Caterpillar TO-2 Fluids, Chrysler transmissions prior to Chrysler MS-9602 or MS-7176, MAN 339 Z1 and V1, Z2 and V2, MB 236.1, 236.5, 236.6, 236.7, 236.9, Voith 55,6335 and 55,6336, Volvo 97340, 97341, ZF TE-ML 02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C and others types of vehicles whose manufacturers recommend this type of oil;
- ensures long life for components subject to wear;
- excellent oxidative stability, ensuring protection against corrosion or sediment deposits.

APPLICATION

- recommended for all types of automatic transmissions and power steering systems of cars and vans, industrial equipment that require an oil corresponding to the above requirements;
- recommended for hydraulic systems that require anti-wear oils with good fluidity even at low temperatures.

PROPERTIES

Density at 15°C [kg/m ³], max	860
Kinematic Viscosity at 100°C [mm ² /s]	7 – 12.5
Viscosity Index	180
Flash Point [°C]	210
Pour Point [°C]	-42
Brookfield Viscosity at -40°C [mPa.s]	20000
Colour	red

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg	<input checked="" type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input checked="" type="checkbox"/> 208l	<input checked="" type="checkbox"/> 1000l
<input type="checkbox"/> 4l	<input checked="" type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.