



HEXOL UTTO 80W – 10W30 PREMIUM

UNIVERSAL TRACTOR OIL

PRODUCT DESCRIPTION

HEXOL UTTO 80W - 10W30 Premium is a transmission oil with special properties, recommended for year-round use in agricultural machinery or other machinery whose manufacturer recommends lubrication with such an oil. It is compatible in machinery equipped with wet brakes. It contains high-quality mineral oils and specific additives.

PERFORMANCE FEATURES

- can be used for API GL-4 specifications, John Deere J-20C, J-20D; Case New Holland MAT 3525 (134-D Fluid, Multi-G, Multi-G 134), MAT 3526, ESN M2C86B, C; Case New Holland (ZINC FREE), MAT 3505, MAT 3540; AGCO Massey-Ferguson M-1145, White Q-1826; Volvo VCE 1273.03, WB-101, WB-102; Eaton Vickers; ZF TE-ML-03E, 03F, 05F, 06E, 06F, 06K, 17E, 21F; Allison C-4, Caterpillar; Kubota UDT, Super UDT, Super UDT2, JCMAS HK P-041 & P-042; Parker (Denison) HF-0, HF-1, HF-2 and other types of vehicles or equipment whose manufacturers recommend the use of an oil with this classification.

APPLICATION

- intended for agricultural, industrial, construction machinery as well as any other machinery where the manufacturer recommends the use of an oil with the above specifications;
- it is recommended to use it all year round.

PROPERTIES

Viscosity Grade	SAE 80W – 10W30
API Service	GL-4
Density at 15°C [kg/m ³], max	900
Kinematic Viscosity at 100°C [mm ² /s]	9.3 – 12.5
Viscosity Index	130
Flash Point [°C]	210
Pour Point [°C]	-25

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 208l	<input type="checkbox"/> 1000l
<input type="checkbox"/> 4l	<input type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.